Agents

Engineering Non-Deterministic Software

Saksham Dhull · AI Agents, WisdomAI



Introduction

I'm **Saksham Dhull**. I lead the AI Agents team at **WisdomAI**, where we build agents for data analysis and business intelligence. I graduated from IIT Delhi in 2021 and have been in the tech industry for around five years now.

In this session, we'll understand what an AI agent consists of and the process to build one. Then we'll build a small first version, and follow the same system as its complexity grows.

Our running example is a **coding agent**: it starts as an independent Bash-script-writing agent and evolves into a production-grade SWE agent.



1

Agent fundamentals

what is an agent · choosing the model · designing tools · writing instructions · when do we need one



What is an agent?

1.1

An **agent** is a system that uses an LLM to choose actions, receives feedback from those actions, and continues towards a goal.

Conventional software



All actions and their workflows are pre-defined and programmatically executed, so every request behaves **deterministically**.

An agent



An LLM is **non-deterministic**: it can produce different results for the same task, so the same request can follow different paths across attempts.

An agent has 3 core parts

1.1

Instructions

Describe the task at hand, the LLM's roles and responsibilities, and the constraints.

Model

The reasoning engine that analyses the instructions to choose the next action or response.

Tools

Pre-defined workflows that let the model perform tasks outside its reasoning loop.



We combine these three in a loop to build an agent.

Choosing the model

1.2

The model is the reasoning unit in an agentic system. Model choice affects **task quality, tool use, latency and cost**.

Start with the most capable model available, then compare alternatives on your own tasks.

Benchmarks help shortlist models, but **evaluations** tell us how they perform inside our agent.

In later slides, we'll use these evaluations to optimise our model selection and achieve the best trade-off between cost, latency and quality.



Source: Artificial Analysis, 11 Nov 2026

Designing tools

1.3

Tools are functions an agent can request to retrieve information or perform actions. A tool may combine several operations into one useful workflow.



A tool is defined by:

Name

States what operation this tool performs.

e.g.

```
list-files
```

Description

Describes what it does, when to use it, what it returns and what it changes.

e.g.

```
List files in a project directory. Use this to inspect available files in a given directory. Returns relative file paths; does not modify files.
```

Arguments

The inputs it accepts. Each argument has a name, type and description, and can be required or optional.

e.g.

```
directory: a string path relative to the project root; . selects the root.
```

The model asks; our system executes

1.3

The model never executes the function or the tool call itself. It generates a structured request:

```
{
  "type": "tool",
  "call_id": "call_0123",
  "name": "list-files",
  "arguments": {
    "directory": "."
  }
}
```

1. Our system checks the arguments and permissions.
2. It executes the function.
3. It returns the result, or the error, with the corresponding `call_id`.
4. The model uses that feedback to choose its next step.



Guiding principle

Describe the tool clearly enough that someone unfamiliar with your system can understand when to use it, what inputs it needs and what its result means.

Writing instructions

1.4

Instructions (context) reach an agent as 3 message types:

System prompt

Instructions about the role and purpose of the agent, constraints and completion guidance.

User prompt

The task or goal assigned by the user, inputs provided and user preferences.

Tool results

Results from the tool calls made by the LLM.

Use clear, specific language, and examples where a requirement could be misunderstood.

Improve the instructions using failures found during evaluation.



Instructions only guide.
Code enforces.

Important restrictions must always be enforced in code. Telling the agent not to modify files is different from giving it read-only access.

When do we need an agent?

1.5

Agents are great at executing ambiguous requests. However, not every request in software is ambiguous. So when should we use an agent, and when a programmatic approach?



Programmatic

A task which follows known paths and can be modelled into a decision tree.



Agent

The next action depends on information discovered during the task: investigating an unfamiliar problem, adapting after feedback.

The question is not just whether an agent can perform the task, but whether letting the model choose the next steps offers enough benefit over a programmatic approach to justify the additional **cost, latency and complexity**.

Example: a maps application

1.5



A routing algorithm can calculate the best route between locations; we do not need an LLM to reason through every road.

A language model could be used to interpret ambiguous requests into a structured request, while location and routing services handle the lookup and calculation programmatically.

2

Steps to build an agent

define the task · define success · build the agent



Step 1: Define the task



Write down the supported requests, range of tasks, required results, limits and stopping conditions. These requirements give us something concrete to build and check.

The more detailed your task definition is, the better agent you'll build from the start.

Ambiguity kills iteration speed.



Our coding agent, v1



1. Takes a natural-language request and writes a single Bash script, tests it in an isolated workspace, and returns the script with its results.
2. If it cannot complete or verify the task, it reports what failed.

Scope: a single script in a disposable test workspace. It cannot modify an existing project or execute against the user's real files.

Step 2: Defining success



Once we have defined what the agent should do, we need a way to check how well it does it. A few successful requests are not enough to judge the entire system: we need to understand which tasks it struggles with and whether any changes actually improve it.

Evaluations give us a repeatable way to make that comparison. An evaluation set is a collection of cases covering the expected behaviour from the agent. It should include general requests, edge cases and failure situations.

In general, we care about these 4 knobs:



Correctness

How often does the agent match the expected behaviour?



Quality

Is the result clear, useful and appropriately scoped?



Latency

How long does the attempt take, including repairs and tool calls?



Cost

How much does the average attempt cost?

Judge the outcome, not the path

2

Because agents are non-deterministic, the same request may produce different valid scripts. We evaluate **whether the requirements are met**, not whether the code or execution path matches a given reference.

Example task: write a script that gives the sum of the first 10 natural numbers.

```
#!/bin/bash
sum=0
for i in {1..10}; do
  sum=$((sum + i))
done
echo "$sum"
```

✓ prints 55: requirement met

or

```
#!/bin/bash
n=10
echo $(( n * (n + 1) / 2 ))
```

✓ prints 55: requirement met

Step 3: Building the agent



With the task and evaluation criteria defined, we can connect the components introduced earlier:



Model

Choose a capable starting model that can write scripts and request tools.



Instructions

Write and test one standalone Bash script; report what cannot be completed or verified. Requests requiring an existing codebase or linked scripts are outside this first version's scope.



Tools

`save_script` saves the generated script in the test workspace; `execute_script` runs that version on test inputs and returns results or errors.



The agent loop

2

```
tools = [save_script, execute_script]
context = [instructions, user_request]
for step in range(MAX_STEPS):
    response = model(context, tools)
    context.append(response)
    if response.is_final:
        break
    else if response.is_tool_call:
        result = execute(response.tool_call)
        context.append(result)
return parse(context)
```

The application passes the instructions, request and available tools to the model, then runs this loop.

`execute` checks the requested tool, arguments and permissions, then runs it in the isolated workspace with an execution timeout.

The model chooses the next action;
the application executes it.



Following one request

2



Request: "Write a Bash script that prints the integers from 1 to 100, one per line."

A possible execution could be:

1. **Save:** the model requests `save_script` with its proposed code. The tool returns the saved version's ID.
2. **Test:** the model requests `execute_script` for that version. Suppose the result shows that the output stops at 99.
3. **Revise:** the next model call receives the signal that the script only prints till 99. It then requests `save_script` with a corrected script, creating a new version.
4. **Retest:** the execute tool now runs the new version and attaches the output that stops at 100.
5. **Return:** the model finishes; the application returns the latest script with that version's actual test status.

Save → Test → Reflect → Revise → Retest → Return

Evaluation set

2

For our current agent, an eval set could look something like:

Request	Expectation
Print numbers from 1 to 100	Printed output contains all numbers from 1 to 100, both included.
A script that takes text input and reverses it.	**PASS:** code-based testing with a few examples and edge cases.
Modify the file `test.sh` to add a print `Hello World` at the end.	**FAIL:** the model must fail to create such a script and indicate that it doesn't have the ability to modify system files.

Once this narrow version meets its checks, we have a **baseline** to extend. Now, we'll extend the same agent incrementally and explore the challenges at each stage.

3 Extending our agent

expanding capabilities · longer tasks · from sandbox to production · optimising performance



Expanding capabilities

3.1

Our first agent generated and tested standalone Bash scripts. Now we want it to work inside an existing codebase, where it must explore files, make changes and verify them. To support this, we'll expand its capabilities and reconsider the tools available to it.

New tasks:



Explore

Given a directory, it should be able to list directories, read files and understand existing code.

Modify

Create and edit files within the working directory.

Execute & validate

Run commands and tests, and inspect failures.

Work with Git

Inspect changes, view diffs and manage commits within the directory.

More tools, more choices

3.1

These capabilities warrant new tools, such as `list-files`, `read-file`, `write-file` and `execute_command`.

Git operations could have their own tools, such as `create-branch`, `create-commit`, `delete-branch`, `view-diff`. But if our agent already has `execute_command`, it can perform these operations through Git commands.

As we expand the toolset, the model has more choices to make. If two tools have overlapping responsibilities or unclear descriptions, it will confuse the model.

Retaining both `execute_script` and `execute_command` creates confusion: which should the model use to run a Bash file? Similarly for `save-script` and `write-file`.



So we decommission both initial tools and evaluate the performance.



execute_script and save-script: retired

Principles for better tool design

3.1.1

Design for the model



A tool should be understandable to someone unfamiliar with the system. Its description should explain when to use it, what inputs it expects, what it returns and what it changes. Ambiguity here directly affects the model's decisions. Improving tool descriptions has the greatest effect on tool performance and error rates.

Choose the right level of abstraction



A thoughtfully designed tool will always outperform many smaller ones that require repeated calls. A `search_files` tool is preferable to repeatedly calling `list_files` and `read_file` to locate a keyword. Every unnecessary call adds latency and another opportunity for failure.

Keep tool outputs crisp



A tool should only output information relevant to the agent's next decision. Returning more information isn't necessarily better. If `list_files` returns hundreds of irrelevant attributes, that consumes context and makes it harder for the agent to work.

Make failures explicit and actionable



A tool should be honest about its results. The agent must be able to understand what happened clearly to decide what to do next.

Regression testing

3.1.2

As we add capabilities and modify tools, we can unintentionally make our agent fail tasks it previously handled well. This is called a **regression**. In an agentic system, even a small change to a tool description or a system prompt can alter the model's decisions.

For example: after replacing `execute_script` with `execute_command`, the agent can now run multiple languages and Git commands. But what if it starts failing the Bash tasks it previously handled correctly?

Since agent behaviour can vary between runs, repeat important evaluation cases to identify flaky behaviour rather than mistaking occasional successes for reliable improvements.

Always retain existing evaluation cases, and add new ones whenever we expand the agent. Use two collections:



A stable core

for regression testing



A growing set

of new tasks and failure cases, to aid the hill climb

Longer tasks

3.2

Our agent can now explore repositories, modify files and execute tests. Let's give it a more complex task:

> "Find the race condition between the rabbit and the tortoise and fix it, then update the relevant tests and verify that the fix doesn't break existing functionality."



Unlike our earlier tasks, this will require the agent to first investigate the code, understand where the critical sections are and how they can be remodelled without affecting the existing functionality. Then it will also need to update the tests and verify that everything works well.

As tasks get longer, three challenges become increasingly important:

1. **Planning**
   How do we break the task into smaller steps and track progress?
2. **Context and memory**
   How do we preserve relevant information across multiple steps without overwhelming the model?
3. **Reliability and reflection**
   How do we recover from mistakes and verify that the entire task succeeded?

Planning

3.2.1

As tasks become more complex, the agent needs to coordinate multiple steps, track dependencies and remember what's left to do. Without a plan, it may repeat work, overlook requirements or make changes in the wrong order.

Think of directing a friend to this lecture hall. They could find it by exploring the campus and checking every room, or maybe asking every person they meet on the way.

But giving them a plan to first check with a guard, then look for sign-posts and landmarks makes their journey more predictable and potentially faster.



a plan makes the journey more predictable

Planning in the system prompt

3.2.1

For our agent, we'll add to the system prompt:

```
For complex tasks:
1. Inspect the problem and create a plan with
   smaller steps.
2. Execute the steps and keep record of the
   progress and the complications.
3. Revise the plan when new information emerges.
4. Run the relevant tests and verify the result
   before reporting completion.
```



A plan guides; it doesn't dictate.

A plan only guides the execution; it shouldn't rigidly dictate every action. The agent must still adapt to what it discovers.

For longer tasks, our system can persist the plan and progress so they remain available across model calls.

Context management

3.2.2

As our agent investigates the race condition, it accumulates code snippets, tool outputs, failed attempts and revised hypotheses. Over time, its context grows with information that may no longer be relevant.

This creates two problems:

- **Context pollution:** irrelevant or outdated information makes it harder for the model to identify what matters.
- **Context window limit:** models can only process a finite amount of information in each call. We cannot keep adding the entire execution history indefinitely.



the right information at the right time

Keep, summarize, discard

3.2.2

Context management means selecting the information the model needs for its next decision. The goal is to provide the model with the right information at the right time. For this, we divide the context into 3 parts:



We can't keep the entire execution history in the model's context. But discarding information permanently isn't ideal either. What if our agent needs to revisit an earlier finding or dig deeper into something we have summarized?

That's served using agent memory.

Multi-step reliability and reflection

3.2.3

As our agent takes on longer tasks, it makes more decisions, executes more tools and modifies more files. Each additional step creates another opportunity for something to go wrong.

Consider a simplified example: an agent needs to complete **20 steps**, each with a **95%** probability of success. Assuming independent steps and no recovery:

P(all steps succeed)

$$0.95^{20} \approx 36\%$$



Recovering with reflection

3.2.3

An agent making a mistake is expected; what matters is how it recovers from such failures. For this, we add instructions for **reflection**, asking the agent to examine the failure, identify what went wrong and revise its approach instead of simply retrying the same steps.

For our agent, we add to the system prompt:

```
When an action fails:
1. Examine the error and relevant feedback.
2. Identify the likely cause of failure.
3. Formulate a revised plan and retry.
4. Verify the result.
```

Verifiable feedback makes recovery more effective

For our coding agent, unit tests provide objective signals about whether a change works. The agent can use failing tests to investigate problems, revise its approach and verify the result rather than relying solely on its own judgment.



From sandbox to production

3.3

So far, our agent has operated in a controlled environment. Now we want real users to connect their repositories, request code changes and use the results. This introduces two important security challenges:



Protect our system from untrusted inputs

Repository files, dependencies and external documentation could contain malicious instructions designed to manipulate the agent.

Protect users from unintended agent actions

Our agent can now modify files, execute commands and access external services. A mistake or excessive permissions could lead to data loss, leaked credentials or unauthorized changes.

Never trust input by default.

We must validate external data, restrict permissions and enforce boundaries around what the agent can execute. The goal is to ensure the agent operates safely within the permissions it has been given.

Prompt injection

3.3.1

Our coding agent would read README files, source code and documentation to understand a repository. But what if one of those files tries to instruct the agent instead of describing the project?

This is **prompt injection**: instructions embedded in lower-trust content attempting to redirect the model away from the user's actual task. The file is relevant to the investigation, but its contents are **data, not authority**.

To limit the risk, we put defenses at two levels:

- **Instructions:** tell the model that repository files, tool outputs and input data are untrusted. Any instructions found inside them should not override the user's task.
- **Execution:** enforce sensitive restrictions in code. For example, `read_file` should reject attempts to access `.env` files or paths outside the authorized workspace.



Permissions and guardrails

3.3.2

Agents dynamically decide which tools to use and what commands to execute. A misunderstood request, incorrect tool choice or malicious instruction could lead to deleted files, exposed credentials or unverified code being published. We need to control what the agent is authorised to do:



IAM

identity and access management

Determines who is making a request and what resources they can access. When our agent acts on behalf of a user, it must operate within that user's authorised permissions. For example, a developer with read-only repository access shouldn't be able to use the agent to push code.



Sandboxing

Controls where and how commands execute. Our agent can compile and test untrusted code inside an isolated environment without granting it unrestricted access to the host filesystem, secrets or network.



Guardrails and approval

Control which actions require additional checks. Reading source code may be permitted automatically, while deleting branches or pushing code could require explicit user approval.

Optimising performance

3.4

Our coding agent can now investigate repositories, fix bugs and work with real user projects. But as we increase its capabilities, individual requests can become slower and more expensive.

As we move to production, the trade-offs between **latency, cost and capability** immediately become highly relevant.

Three places to look:

- Model optimisation
- Execution modes
- Reducing and reusing work



Model optimisation

3.4.1

Earlier, we chose the most capable model available to establish a baseline. Once our agent performs reliably, we can optimise for latency and cost. For this, we use a systematic approach:

1. **Establish a baseline:** run our evaluation set with the capable model. Record success rate, latency, cost and traces.
2. **Identify opportunities:** inspect traces to find simple, repetitive subtasks that don't require advanced reasoning.
3. **Experiment with smaller models:** replace the model for those subtasks while keeping the rest of the agent unchanged.
4. **Compare evaluations:** measure whether the new configuration maintains task quality while reducing end-to-end latency and cost.
5. **Keep or revert:** retain changes that improve the trade-off; revert those that introduce unacceptable failures.

For our coding agent, this could look like:

Investigating a complex race condition

→ **capable reasoning model**

Classifying file-search results

→ **potentially smaller model**

Verifying tests

→ **deterministic code, no LLM required**

Execution modes

3.4.2

Sometimes, optimising for lower latency and cost comes at the expense of capability. Instead of forcing one trade-off on everyone, we can offer different modes. For our coding agent:

	Lite	Normal	Expert
Model	Fast, inexpensive	Balanced	Most capable
Tools	Basic file editing and tests	Repository exploration, Git and tests	Full authorised toolset
Instructions	Bounded, simple tasks	Standard investigation and repair	Deeper investigation and verification



The modes can share the same underlying agent architecture while differing in models, tools, instructions and execution budgets.

Reducing and reusing work

3.4.3

After choosing the right model and execution mode, we can still waste time on unnecessary model calls, repeated tool operations and work we've already completed.

Measure the whole attempt

Separate time spent in model calls, file operations, tests and retries. Optimise the bottleneck rather than assuming model inference is the slowest part.

Remove redundant steps

Avoid rereading unchanged files or repeating failed commands without new information. Run independent searches or tests in parallel, but keep dependent operations sequential.

Cache repeated inputs

Stable system instructions and tool definitions can benefit from provider-supported **prompt caching**, reducing eligible input-processing cost and sometimes latency. The model still generates a new response.

Reuse tool results carefully

A file search can be reused if the relevant repository state hasn't changed. Once files change, cached search results may be stale, and tests from an earlier code version cannot verify the new one.

The goal isn't the fewest possible calls. It's the least work required to achieve a verified result.

Summary

4

We started with a small Bash-script agent and extended it into a coding agent that can work with repositories. Along the way, each new capability introduced new engineering decisions:



Expanding capabilities

Add or consolidate tools based on the tasks we want to support, then run regression evaluations to catch broken behaviour.



Longer tasks

Use planning, context management and reflection to coordinate work, preserve relevant findings and recover from failures.



From sandbox to production

Treat repository content as untrusted, enforce permissions outside the model and limit what commands can do.



Optimising performance

Start with a capable baseline, evaluate smaller models and subtasks, offer execution modes where trade-offs matter, and reduce repeated work through caching.

The recurring development loop

4



Each addition should solve a real problem and earn its complexity through measurable results.

Where to advance from here



Topics worth exploring further:

Agent architectures: ReAct, planning, reflection, multi-agent systems and orchestration.

Context engineering: memory, retrieval, context compression and long-running agents.

Evaluations: LLM-as-a-judge, benchmark design, failure analysis and regression testing.

Tooling and protocols: MCP, tool design, sandboxing and permission management.

Production engineering: observability, prompt caching, latency optimization, reliability and scaling.



?

Questions

thank you · Saksham Dhull, WisdomAI

